

Conductive Polymer Hybrid Aluminum Electrolytic Capacitors HV1,HT1 series

Code in front of series have been extracted from product code, which describes the segment of products, such as type and features.

Specifications

Item	Performance					
Category temperature range (°C)	-55 to +105					
Tolerance at rated capacitance (%)	±20 (20°C, 120Hz)					
Leakage current (μA) (max.)	0.01CV or 3 whichever is larger (after 2 minutes) C : Rated capacitance (μF) ; V : Rated voltage (V) (20°C)					
Tangent of loss angle (tanδ)	Rated voltage (V)	25	35	50	63	80
	tanδ (max.)	0.14	0.12	0.10	0.08	0.08
(20°C, 120Hz)						
Characteristics at high and low temperature	Impedance ratio (max.)	Z-25°C/Z+20°C		1.5		
		Z-55°C/Z+20°C		2.0		
(100kHz)						
Endurance (105°C) (Applied ripple current)	Test time	10000 hours				
	Leakage current	The initial specified value or less				
	Percentage of capacitance change	Within ±30% of initial value				
	Tangent of the loss angle	200% or less of the initial specified value				
	ESR change	200% or less of the initial specified value				
Shelf life (105°C)	Test time : 1000hours ; other items are same as the endurance. Voltage application treatment : According to JIS C5101-4 4.1.					