

Code in front of series have been extracted from product code, which describes the segment of products, such as type and features.

Specifications

Item	Performance										
Category temperature range (°C)	-55 to +125										
Tolerance at rated capacitance (%)	±20 (20°C, 120Hz)										
Leakage current (µA) (max.)	0.01CV or 3 whichever is larger (after 2 minutes) C : Rated capacitance (µF) ; V : Rated voltage (V) (20°C)										
Tangent of loss angle (tan δ)	<table border="1"> <thead> <tr> <th>Rated voltage (V)</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> </tr> </thead> <tbody> <tr> <td>tan δ (max.)</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.08</td> </tr> </tbody> </table> (20°C, 120Hz)	Rated voltage (V)	25	35	50	63	tan δ (max.)	0.14	0.12	0.10	0.08
Rated voltage (V)	25	35	50	63							
tan δ (max.)	0.14	0.12	0.10	0.08							
Characteristics at high and low temperature	Impedance ratio (max.) <table border="1"> <tbody> <tr> <td>Z-25°C/Z+20°C</td> <td>1.5</td> </tr> <tr> <td>Z-55°C/Z+20°C</td> <td>2.0</td> </tr> </tbody> </table> (100kHz)	Z-25°C/Z+20°C	1.5	Z-55°C/Z+20°C	2.0						
Z-25°C/Z+20°C	1.5										
Z-55°C/Z+20°C	2.0										
Endurance (125°C) (Applied ripple current)	<table border="1"> <tbody> <tr> <td>Test time</td> <td>8000 hours</td> </tr> <tr> <td>Leakage current</td> <td>The initial specified value or less</td> </tr> <tr> <td>Percentage of capacitance change</td> <td>Within ±30% of initial value</td> </tr> <tr> <td>Tangent of the loss angle</td> <td>200% or less of the initial specified value</td> </tr> <tr> <td>ESR change</td> <td>200% or less of the initial specified value</td> </tr> </tbody> </table>	Test time	8000 hours	Leakage current	The initial specified value or less	Percentage of capacitance change	Within ±30% of initial value	Tangent of the loss angle	200% or less of the initial specified value	ESR change	200% or less of the initial specified value
Test time	8000 hours										
Leakage current	The initial specified value or less										
Percentage of capacitance change	Within ±30% of initial value										
Tangent of the loss angle	200% or less of the initial specified value										
ESR change	200% or less of the initial specified value										
Shelf life (125°C)	Test time : 1000hours ; other items are same as the endurance. Voltage application treatment : According to JIS C5101-4 4.1.										

NOTE : Design, Specifications are subject to change without notice.
It is recommended that you shall obtain technical specifications from ELNA to ensure that the component is suitable for your use.