

Notice for TAIYO YUDEN Products

Please read this notice before using the TAIYO YUDEN products.



REMINDERS

Product Information in this Catalog

Product information in this catalog is as of March 2023. All of the contents specified herein and production status of the products listed in this catalog are subject to change without notice due to technical improvement of our products, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

Approval of Product Specifications

Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available. When using our products, please be sure to approve our product specifications or make a written agreement on the product specification with TAIYO YUDEN in advance.

Pre-Evaluation in the Actual Equipment and Conditions

Please conduct validation and verification of our products in actual conditions of mounting and operating environment before using our products.

Limited Application

1. Equipment Intended for Use

The products listed in this catalog are intended for general-purpose and standard use in general electronic equipment for consumer (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and other equipment specified in this catalog or the individual product specification sheets, or the equipment approved separately by TAIYO YUDEN.

TAIYO YUDEN has the product series intended for use in the following equipment. Therefore, when using our products for these equipment, please check available applications specified in this catalog or the individual product specification sheets and use the corresponding products.

Application	Product Series		Quality Grade ^{*3}
	Equipment ^{*1}	Category (Part Number Code ^{*2})	
Automotive	Automotive Electronic Equipment (POWERTRAIN, SAFETY)	A	1
	Automotive Electronic Equipment (BODY & CHASSIS, INFOTAINMENT)	C	2
Industrial	Telecommunications Infrastructure and Industrial Equipment	B	2
Medical	Medical Devices classified as GHTF Class C (Japan Class III)	M	2
	Medical Devices classified as GHTF Classes A or B (Japan Classes I or II)	L	3
Consumer	General Electronic Equipment	S	3
	Only for Mobile Devices ^{*4}	E	4

^{*Notes:} 1. Based on the general specifications required for electronic components for such equipment, which are recognized by TAIYO YUDEN, the use of each product series for the equipment is recommended. Please be sure to contact TAIYO YUDEN before using our products for equipment other than those covered by the product series.

2. On each of our part number, the 2nd code from the left is a code indicating the "Category" as shown in the above table. For details, please check the explanatory materials regarding the part numbering system of each of our products.

3. Each product series is assigned a "Quality Grade" from 1 to 4 in order of higher quality. Please do not incorporate a product into any equipment with a higher Quality Grade than the Quality Grade of such product without the prior written consent of TAIYO YUDEN.

4. The applications covered by this product series are limited to mobile devices (smartphone, tablet PC, smartwatch, handheld game console, etc.) among general electronic equipment for consumer. The design, specifications and operating environment, etc. differ from those of the product series for "General Electronic Equipment" (Category: S), so please check the individual product specification sheets for details. The product series for "General Electronic Equipment" (Category: S) can also be used for mobile devices.

2. Equipment Requiring Inquiry

Please be sure to contact TAIYO YUDEN for further information before using the products listed in this catalog for the following equipment (excluding intended equipment as specified in this catalog or the individual product specification sheets) which may cause loss of human life, bodily injury, serious property damage and/or serious public impact due to a failure or defect of the products and/or malfunction attributed thereto.

- (1) Transportation equipment (automotive powertrain control system, train control system, and ship control system, etc.)
- (2) Traffic signal equipment
- (3) Disaster prevention equipment, crime prevention equipment
- (4) Medical devices classified as GHTF Class C (Japan Class III)
- (5) Highly public information network equipment, data-processing equipment (telephone exchange, and base station, etc.)
- (6) Any other equipment requiring high levels of quality and/or reliability equal to the equipment listed above

3. Equipment Prohibited for Use

Please do not incorporate our products into the following equipment requiring extremely high levels of safety and/or reliability.

- (1) Aerospace equipment (artificial satellite, rocket, etc.)
- (2) Aviation equipment ^{*1}
- (3) Medical devices classified as GHTF Class D (Japan Class IV), implantable medical devices ^{*2}
- (4) Power generation control equipment (nuclear power, hydroelectric power, thermal power plant control system, etc.)
- (5) Undersea equipment (submarine repeating equipment, etc.)
- (6) Military equipment
- (7) Any other equipment requiring extremely high levels of safety and/or reliability equal to the equipment listed above

*Notes: 1. There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

2. Implantable medical devices contain not only internal unit which is implanted in a body, but also external unit which is connected to the internal unit.

4. Limitation of Liability

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment that is not intended for use by TAIYO YUDEN, or any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

Safety Design

When using our products for high safety and/or reliability-required equipment or circuits, please fully perform safety and/or reliability evaluation. In addition, please install (i) systems equipped with a protection circuit and a protection device and/or (ii) systems equipped with a redundant circuit or other system to prevent an unsafe status in the event of a single fault for a failsafe design to ensure safety.

Intellectual Property Rights

Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.

Limited Warranty

Please note that the scope of warranty for our products is limited to the delivered our products themselves conforming to the product specifications specified in the individual product specification sheets, and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a failure or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement, provided, however, that our products shall be used for general-purpose and standard use in the equipment specified in this catalog or the individual product specification sheets.

TAIYO YUDEN's Official Sales Channel

The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.

Caution for Export

Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).

Industrial Application Guide

We have the product series (the 2nd code from the left side of the part number is “B”) intended for use in telecommunications infrastructure and industrial equipment (its typical examples are as shown in the table below). Therefore, when using our products for these equipment, please check it carefully by referring to the part number or the individual product specification sheets and use the corresponding product series. Should you have any questions on this matter, please contact us.

Product Series (The 2nd Code from the Left Side of the Part Number)	Category	Telecommunications Infrastructure and Industrial Equipment (Typical Example)
B	Telecommunications Infrastructure	<ul style="list-style-type: none">• Base Station• Optical Transceiver• Router/Switch (Carrier-Grade)• UPS (Uninterruptible Power Supply), etc.
	Factory Automation	<ul style="list-style-type: none">• PLC (Programmable Logic Controller)• Servomotor/Servo Driver• Industry Robot, etc.
	Measurement	<ul style="list-style-type: none">• Gas Meter• Water Meter• Flow Meter• Pressure Gauge Meter• Magnetometer• Thermometer, etc.
	Electric Power Apparatus	<ul style="list-style-type: none">• Power Conditioner (Solar Power System)• Smart Meter• GFCI (Ground Fault Circuit Interrupter)• Electric Vehicle Charging Station, etc.

Wire-wound Ferrite Inductors for Signal Lines LBQM series

for Telecommunications Infrastructure and Industrial Equipment

Code in front of Series have been extracted from Part number, which describes the segment of products, such as kinds and characteristics.

REFLOW

PART NUMBER

*Operating Temp. : -40~105°C(Including self-generated heat)

L	B	Q	M	B	2	0	1	6	1	6	T	1	0	0	J	
①	②	③	④	⑤	⑥	⑦	⑧									

①Series

Code (1)(2)(3)(4)	
LBQM	Wire-wound Ferrite Inductor for Telecommunications Infrastructure and Industrial Equipment

(1) Product Group

Code	
L	Inductors

(3) Type

Code	
Q	Ferrite Wire-wound (Horizontal type)

(2) Category

Code	Recommended equipment	Quality Grade
B	Telecommunications Infrastructure and Industrial Equipment	2

(4) Features, Characteristics

Code	
M	Signal line

②Features

Code	Feature
B	L-shape electrode (Ag-resin × Sn-plate)

⑤Packaging

Code	Packaging
T	Taping

③Dimensions (L × W)

Code	Type (inch)	Dimensions (L × W) [mm]
2016	2016(0806)	2.0 × 1.6

⑥Nominal inductance

Code (example)	Nominal inductance [μH]
R12	0.12
1R0	1.0
100	10
101	100

※R=Decimal point

④Dimensions (T)


Code	Dimensions (T) [mm]
16	1.6

⑦Inductance tolerance

Code	Inductance tolerance
J	±5%

⑧Internal code

STANDARD EXTERNAL DIMENSIONS / STANDARD QUANTITY




Recommended Land Patterns

Surface Mounting

- Mounting and soldering conditions should be checked beforehand.
- Applicable soldering process to these products is reflow soldering only.

Type	A	B	C
2016	0.6	1.0	1.8

Unit: mm



Type	L	W	T	e	Standard quantity [pcs]	
					Paper tape	Embossed tape
201616	2.0±0.2 (0.08±0.008)	1.6±0.2 (0.063±0.008)	1.6±0.2 (0.063±0.008)	0.5±0.2 (0.02±0.008)	—	2000

Unit: mm (inch)

PART NUMBER

- All the Wire-wound Ferrite Inductors for Signal Lines of the catalog lineup are RoHS compliant.

Notes)

- The exchange of individual specifications is necessary depending on your application and/or circuit condition. Please contact TAIYO YUDEN's official sales channel.
- The products are for Telecommunications infrastructure and Industrial equipment.
Please consult with TAIYO YUDEN's official sales channel for the details of the product specifications, etc., and please review and approve the product specifications before ordering.

2016(0806) type

New part number	Old part number (for reference)	Nominal inductance [μ H]	Inductance tolerance	Q (min.)	Self-resonant frequency [MHz] (min.)	DC Resistance [Ω] ($\pm 30\%$)	Rated current [mA] (max.)	Measuring frequency [MHz]
LBQMB201616TR12J	LBM 2016TR12J 8	0.12	$\pm 5\%$	30	600	0.13	610	25.2
LBQMB201616TR15J	LBM 2016TR15J 8	0.15	$\pm 5\%$	30	550	0.15	570	25.2
LBQMB201616TR18J	LBM 2016TR18J 8	0.18	$\pm 5\%$	30	500	0.15	560	25.2
LBQMB201616TR22J	LBM 2016TR22J 8	0.22	$\pm 5\%$	30	450	0.20	520	25.2
LBQMB201616TR27J	LBM 2016TR27J 8	0.27	$\pm 5\%$	30	425	0.21	510	25.2
LBQMB201616TR33J	LBM 2016TR33J 8	0.33	$\pm 5\%$	30	400	0.21	490	25.2
LBQMB201616TR39J	LBM 2016TR39J 8	0.39	$\pm 5\%$	30	375	0.26	440	25.2
LBQMB201616TR47J	LBM 2016TR47J 8	0.47	$\pm 5\%$	30	350	0.26	430	25.2
LBQMB201616TR56J	LBM 2016TR56J 8	0.56	$\pm 5\%$	30	300	0.29	410	25.2
LBQMB201616TR68J	LBM 2016TR68J 8	0.68	$\pm 5\%$	30	270	0.32	400	25.2
LBQMB201616TR82J	LBM 2016TR82J 8	0.82	$\pm 5\%$	30	250	0.34	390	25.2
LBQMB201616TR1R0J	LBM 2016TR1R0J 8	1.0	$\pm 5\%$	30	220	0.38	385	7.96
LBQMB201616TR1R2J	LBM 2016TR1R2J 8	1.2	$\pm 5\%$	30	180	0.41	370	7.96
LBQMB201616TR1R5J	LBM 2016TR1R5J 8	1.5	$\pm 5\%$	30	135	0.47	350	7.96
LBQMB201616TR1R8J	LBM 2016TR1R8J 8	1.8	$\pm 5\%$	30	100	0.48	345	7.96
LBQMB201616TR2R2J	LBM 2016TR2R2J 8	2.2	$\pm 5\%$	30	75	0.54	340	7.96
LBQMB201616TR2R7J	LBM 2016TR2R7J 8	2.7	$\pm 5\%$	30	55	0.59	310	7.96
LBQMB201616TR3R3J	LBM 2016TR3R3J 8	3.3	$\pm 5\%$	30	48	0.68	290	7.96
LBQMB201616TR3R9J	LBM 2016TR3R9J 8	3.9	$\pm 5\%$	30	43	0.74	275	7.96
LBQMB201616TR4R7J	LBM 2016TR4R7J 8	4.7	$\pm 5\%$	30	40	0.78	270	7.96
LBQMB201616TR5R6J	LBM 2016TR5R6J 8	5.6	$\pm 5\%$	25	36	0.88	255	7.96
LBQMB201616TR6R8J	LBM 2016TR6R8J 8	6.8	$\pm 5\%$	25	33	0.97	240	7.96
LBQMB201616TR8R2J	LBM 2016TR8R2J 8	8.2	$\pm 5\%$	25	30	1.1	225	7.96
LBQMB201616T100J	LBM 2016T100J 8	10	$\pm 5\%$	25	27	1.2	215	2.52
LBQMB201616T120J	LBM 2016T120J 8	12	$\pm 5\%$	25	23	1.4	200	2.52
LBQMB201616T150J	LBM 2016T150J 8	15	$\pm 5\%$	25	20	1.5	190	2.52
LBQMB201616T180J	LBM 2016T180J 8	18	$\pm 5\%$	25	18	2.5	150	2.52
LBQMB201616T220J	LBM 2016T220J 8	22	$\pm 5\%$	25	17	2.8	140	2.52
LBQMB201616T270J	LBM 2016T270J 8	27	$\pm 5\%$	25	16	3.2	130	2.52
LBQMB201616T330J	LBM 2016T330J 8	33	$\pm 5\%$	25	15	3.6	125	2.52
LBQMB201616T390J	LBM 2016T390J 8	39	$\pm 5\%$	20	14	3.9	120	2.52
LBQMB201616T470J	LBM 2016T470J 8	47	$\pm 5\%$	20	13	4.1	115	2.52
LBQMB201616T560J	LBM 2016T560J 8	56	$\pm 5\%$	20	12	5.9	95	2.52
LBQMB201616T680J	LBM 2016T680J 8	68	$\pm 5\%$	20	11	7.0	90	2.52
LBQMB201616T820J	LBM 2016T820J 8	82	$\pm 5\%$	20	10	7.7	85	2.52
LBQMB201616T101J	LBM 2016T101J 8	100	$\pm 5\%$	15	9.0	8.0	80	0.796


・LBQM series

※) Rated Current: The maximum DC value having inductance decrease within 10 % and temperature increase within 20 degC by the application of DC bias.

Derating of Rated Current

LBQM series

Derating of current is necessary for LBQM series depending on ambient temperature.
Please refer to the chart shown below for appropriate derating of current.



► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) .

Wire-wound Ferrite Inductors LSQB/LSQC/LSQE/LLQB/LLQC/LLQE/LMQB/LMQC/LMQE/
LBQB/LBQC/LBQE series
Wire-wound Ferrite Power Inductors LSQN/LSQPA/LLQN/LLQPA/LMQN/LMQPA/
LBQN/LBQPA series
Wire-wound Ferrite Inductors for Signal Lines LSQM/LLQM/LMQM/LBQM series


PACKAGING

① Minimum Quantity


Type	Standard Quantity [pcs]	
	Paper Tape	Embossed Tape
A322525	—	1000
A321818	—	2000
A251818	—	2000
B201616	—	2000
A201616	—	2000
A201212	—	3000
A201209	4000	—
A160808	4000	—
B160808	—	3000

② Tape material

Embossed tape




Card board carrier tape




► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>) .

● Embossed Tape (0.315 inches wide)




- Card board carrier tape (0.315 inches wide)




i wound CB LB pack e-E10R01

④ Leader and Blank Portion




⑤ Reel Size



⑥ Top Tape Strength

The top tape requires a peel-off force 0.1 to 1.0N in the direction of the arrow as illustrated below.



Wire-wound Ferrite Power Inductors LBQB/LBQC/LBQE series
for Telecommunications Infrastructure and Industrial Equipment

Wire-wound Ferrite Power Inductors LBQN/LBQPA series
for Telecommunications Infrastructure and Industrial Equipment

Wire-wound Ferrite Inductors for Signal Lines LBQM series
for Telecommunications Infrastructure and Industrial Equipment

Wire-wound Ferrite Power Inductors LMQB/LMQC/LMQE series
for Medical Devices classified as GHTF Class C (Japan Class III)

Wire-wound Ferrite Power Inductors LMQN/LMQPA series
for Medical Devices classified as GHTF Class C (Japan Class III)

Wire-wound Ferrite Inductors for Signal Lines LMQM series
for Medical Devices classified as GHTF Class C (Japan Class III)

■ RELIABILITY DATA

1. Operating temperature Range

Specified Value	−40~+105°C (Including self-generated heat)
Test Methods and Remarks	Including self-generated heat

2. Storage Temperature Range (after soldering)

Specified Value	−40~+85°C
Test Methods and Remarks	Wire-wound Ferrite Inductors, Wire-wound Ferrite Power Inductors: Please refer the term of "7. storage conditions" in precautions.

3. Rated Current

Specified Value	Within the specified tolerance
-----------------	--------------------------------

4. Inductance

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : LCR Meter (HP4285A or its equivalent)

5. Q

Specified Value	Wire-wound Ferrite Inductors for Signal Lines: Within the specified tolerance
Test Methods and Remarks	Wire-wound Ferrite Inductors for Signal Lines : Measuring equipment : LCR Meter (HP4285A or its equivalent)


6. DC Resistance

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : DC Ohmmeter (HIOKI 3227 or its equivalent)

7. Self-Resonant Frequency

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : Impedance analyzer (HP4291A or its equivalent)

8.Temperature Characteristic					
Specified Value	LBQMB2016				Inductance change : Within±10%
	LMQMB2016				
	LBQBA2012	LBQEA2012	LBQNA2012	LBQBA2016	Inductance change : Within±20%
	LBQNA2016	LBQBA2518	LBQEA2518	LBQNA2518	
	LBQCA3225	LBQPA3225			
	LMQBA2012	LMQEA2012	LMQNA2012	LMQBA2016	
	LMQNA2016	LMQBA2518	LMQEA2518	LMQNA2518	
	LMQCA3225	LMQPA3225			
	LBQCA2016	LBQPA2016	LBQCA2518	LBQPA2518	Inductance change : Within±25%
	LBQBA3218				
LMQCA2016	LMQPA2016	LMQCA2518	LMQPA2518		
	LMQBA3218				
	LBQCA2012	LBQPA2012			Inductance change : Within±35%
	LMQCA2012	LMQPA2012			
Test Methods and Remarks	Change of maximum inductance deviation in step 1-5				
	Step	Temperature(℃)			
	1	20			
	2	-40			
	3	20 (Reference temperature)			
	4	+85 (Maximum operating temperature)			
	5	20			

9.Rasistance to Flexure of Substrate	
Specified Value	No damage.
Test Methods and Remarks	Warp : 2mm Test substrate : Board according to JIS C0051 Thickness : 1.0mm
	

10.Body Strength	
Specified Value	No damage.
Test Methods and Remarks	Applied force : 10N
	Duration : 10sec.

11.Adhesion of terminal electrode	
Specified Value	No abnormality.
Test Methods and Remarks	Applied force : 10N to X and Y directions
	Duration : 5 sec.
	Test substrate : Printed board

12. Resistance to vibration	
Specified Value	Inductance change : Within $\pm 20\%$ No significant abnormality in appearance.
Test Methods and Remarks	According to JIS C5102 clause 8.2. Vibration type : A Directions : 2 hrs each in X, Y and Z directions. Total: 6 hrs Frequency range : 10 to 55 to 10 Hz (1min.) Amplitude : 1.5mm Mounting method : Soldering onto printed board Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
13. Drop test	
Specified Value	—
14. Solderability	
Specified Value	At least 90% of surface of terminal electrode is covered by new
Test Methods and Remarks	Solder temperature : $245 \pm 5^\circ\text{C}$ Duration : $5 \pm 0.5\text{sec}$ Flux : Ethanol solution with 25% of colophony
15. Resistance to soldering	
Specified Value	Inductance change : Within $\pm 20\%$
Test Methods and Remarks	3 times of reflow oven at 230°C MIN for 40sec. with peak temperature at 260°C for 5sec.
16. Resistance to solvent	
Specified Value	—
Test Methods and Remarks	Solvent temperature : Room temperature Type of solvent : Isopropyl alcohol Cleaning conditions : 90s. Immersion and cleaning.
17. Thermal shock	
Specified Value	Inductance change : Within $\pm 20\%$ No significant abnormality in appearance.
Test Methods and Remarks	$-40 \sim +85^\circ\text{C}$, maintain times 30min. , 100 cycle Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
18. Damp heat life test	
Specified Value	Inductance change : Within $\pm 20\%$ No significant abnormality in appearance.
Test Methods and Remarks	Temperature : $60 \pm 2^\circ\text{C}$ Humidity : $90 \sim 95\% \text{RH}$ Duration : 1000 hrs Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
19. Loading under damp heat life test	
Specified Value	Inductance change : Within $\pm 20\%$ No significant abnormality in appearance.
Test Methods and Remarks	Temperature : $60 \pm 2^\circ\text{C}$ Humidity : $90 \sim 95\% \text{RH}$ Duration : 1000 hrs Applied current : Rated current Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.

20.High temperature life test	
Specified Value	Wire-wound Ferrite Power Inductors, Wire-wound Ferrite Inductors for Signal Lines : Inductance change : Within $\pm 20\%$ No significant abnormality in appearance
Test Methods and Remarks	Temperature : $85 \pm 2^\circ\text{C}$ Duration : 1000 hrs Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
21.Loading at high temperature life test	
Specified Value	Wire-wound Ferrite Inductors : Inductance change : Within $\pm 20\%$ No significant abnormality in appearance
Test Methods and Remarks	Temperature : $85 \pm 2^\circ\text{C}$ Duration : 1000 hrs Applied current : Rated current Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
22.Low temperature life test	
Specified Value	Inductance change : Within $\pm 20\%$ No significant abnormality in appearance.
Test Methods and Remarks	Temperature : $-40 \pm 2^\circ\text{C}$ Duration : 1000 hrs Recovery : At least 2 hrs of recovery under the standard condition after the test, followed by the measurement within 48 hrs.
23.Standard condition	
Specified Value	Standard test conditions Unless specified, Ambient temperature is $20 \pm 15^\circ\text{C}$ and the Relative humidity is $65 \pm 20\%$. If there is any doubt about the test results, further measurement shall be had within the following limits: Ambient Temperature: $20 \pm 2^\circ\text{C}$ Relative humidity: $65 \pm 5\%$ Inductance value is based on our standard measurement systems.

Wire-wound Ferrite Inductors LSQB/LSQC/LSQE/LLQB/LLQC/LLQE/LMQB/LMQC/LMQE/ LBQB/LBQC/LBQE series

Wire-wound Ferrite Power Inductors LSQN/LSQPA/LLQN/LLQPA/LMQN/LMQPA/ LBQN/LBQPA series

Wire-wound Ferrite Inductors for Signal Lines LSQM/LLQM/LMQM/LBQM series

■ PRECAUTIONS

1. Circuit Design

Precautions

- ◆ Verification of operating environment, electrical rating and performance
 1. A malfunction in medical equipment, spacecraft, nuclear reactors, etc. may cause serious harm to human life or have severe social ramifications. As such, any inductors to be used in such equipment may require higher safety and/or reliability considerations and should be clearly differentiated from components used in general purpose applications.
 2. When inductors are used in places where dew condensation develops and/or where corrosive gas such as hydrogen sulfide, sulfurous acid, or chlorine exists in the air, characteristic deterioration may occur. Please do not use inductors under such environmental conditions.
- ◆ Operating Current (Verification of Rated current)
 1. The operating current including inrush current for inductors must always be lower than their rated values.
 2. Do not apply current in excess of the rated value because the inductance may be reduced due to the magnetic saturation effect.
- ◆ Temperature rise

Temperature rise of power choke coil depends on the installation condition in end products.

Make sure that temperature rise of power choke coils in actual end products is within the specified temperature range.

2. PCB Design

Precautions

- ◆ Land pattern design
 1. Please contact any of our offices for a land pattern, and refer to a recommended land pattern of a right figure or specifications.

Technical considerations

- PRECAUTIONS
【Recommended Land Patterns】
- Surface Mounting
 - Mounting and soldering conditions should be checked beforehand.
 - Applicable soldering process to those products is reflow soldering only.

3. Considerations for automatic placement

Precautions

- ◆ Adjustment of mounting machine
 1. Excessive impact load should not be imposed on the products when mounting onto the PC boards.
 2. Mounting and soldering conditions should be checked beforehand.

Technical considerations

1. When installing products, care should be taken not to apply distortion stress as it may deform the products.


4. Soldering

Precautions

- ◆ Reflow soldering (Wire-wound Ferrite Inductors, Wire-wound Ferrite Power Inductors)
 1. For reflow soldering with either leaded or lead-free solder, the profile specified in "point for controlling" is recommended.
- ◆ Recommended conditions for using a soldering iron
 1. Put the soldering iron on the land-pattern. Soldering iron's temperature – Below 350°C Duration-3 seconds or less. The soldering iron should not come in contact with inductor directly.

Technical considerations

- ◆ Reflow soldering (Wire-wound Ferrite Inductors, Wire-wound Ferrite Power Inductors)
 1. Reflow profile



- ◆ Recommended conditions for using a soldering iron
 1. Components can be damaged by excessive heat where soldering conditions exceed the specified range.

5. Cleaning	
Precautions	<ul style="list-style-type: none"> ◆Cleaning conditions Washing by supersonic waves shall be avoided.
Technical considerations	<ul style="list-style-type: none"> ◆Cleaning conditions If washed by supersonic waves, the products might be broken.
6. Handling	
Precautions	<ul style="list-style-type: none"> ◆Handling <ol style="list-style-type: none"> 1. Keep the inductors away from all magnets and magnetic objects. ◆Breakaway PC boards (splitting along perforations) <ol style="list-style-type: none"> 1. When splitting the PC board after mounting inductors, care should be taken not to give any stresses of deflection or twisting to the board. 2. Board separation should not be done manually, but by using the appropriate devices. ◆Mechanical considerations <ol style="list-style-type: none"> 1. Please do not give the inductors any excessive mechanical shocks.
Technical considerations	<ul style="list-style-type: none"> ◆Handling <ol style="list-style-type: none"> 1. There is a case that a characteristic varies with magnetic influence. ◆Breakaway PC boards (splitting along perforations) <ol style="list-style-type: none"> 1. Planning pattern configurations and the position of products should be carefully performed to minimize stress. ◆Mechanical considerations <ol style="list-style-type: none"> 1. There is a case to be damaged by a mechanical shock.
7. Storage conditions	
Precautions	<ul style="list-style-type: none"> ◆Storage <ol style="list-style-type: none"> 1. To maintain the solderability of terminal electrodes and to keep the packing material in good condition, temperature and humidity in the storage area should be controlled. <ul style="list-style-type: none"> ▪ Storage conditions <ul style="list-style-type: none"> Ambient temperature : 0~40°C Humidity : Below 70% RH ▪ The recommended ambient temperature is below 30°C. Even under ideal storage conditions, solderability of products electrodes may decrease as time passes. <p>For this reason, product should be used within 6 months from the time of delivery. In case of storage over 6 months, solderability shall be checked before actual usage.</p>
Technical considerations	<ul style="list-style-type: none"> ◆Storage <ol style="list-style-type: none"> 1. Under a high temperature and humidity environment, problems such as reduced solderability caused by oxidation of terminal electrodes and deterioration of taping/packaging materials may take place.