

Wire-wound Ferrite Power Inductors LSXBH10050 for General Electronic Equipment for Consumer
Wire-wound Ferrite Power Inductors LLXBH10050
for Medical Devices classified as GHTF Classes A or B (Japan Classes I or II)

■ RELIABILITY DATA

1. Operating Temperature Range

Specified Value	−25~+105°C
Test Methods and Remarks	Including self-generated heat

2. Storage Temperature Range

Specified Value	−40~+85°C
Test Methods and Remarks	−5 to 40°C for the product with taping.

3. Rated current

Specified Value	Within the specified tolerance
-----------------	--------------------------------

4. Inductance

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : LCR Meter (HP 4263A or equivalent) Measuring frequency : 100kHz, 1V

5. DC Resistance

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : DC ohmmeter (HIOKI 3227 or equivalent)

6. Self resonance frequency

Specified Value	Within the specified tolerance
Test Methods and Remarks	Measuring equipment : Impedance analyzer/material analyzer (HP4291A or equivalent HP4191A, 4192A or equivalent)

7. Temperature characteristic

Specified Value	Inductance change : Within $\pm 20\%$												
Test Methods and Remarks	<p>Measurement of inductance shall be taken at temperature range within $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$. With reference to inductance value at $+20^{\circ}\text{C}$., change rate shall be calculated. Change of maximum inductance deviation in step 1 to 5</p> <table border="1"> <thead> <tr> <th>Step</th><th>Temperature (°C)</th></tr> </thead> <tbody> <tr> <td>1</td><td>20</td></tr> <tr> <td>2</td><td>Minimum operating temperature</td></tr> <tr> <td>3</td><td>20 (Standard temperature)</td></tr> <tr> <td>4</td><td>Maximum operating temperature</td></tr> <tr> <td>5</td><td>20</td></tr> </tbody> </table>	Step	Temperature (°C)	1	20	2	Minimum operating temperature	3	20 (Standard temperature)	4	Maximum operating temperature	5	20
Step	Temperature (°C)												
1	20												
2	Minimum operating temperature												
3	20 (Standard temperature)												
4	Maximum operating temperature												
5	20												

8. Resistance to flexure of substrate

Specified Value	—
-----------------	---

9. Insulation resistance : between wires

Specified Value	—
-----------------	---

10. Insulation resistance : between wire and core

Specified Value	—
-----------------	---

11. Withstanding voltage : between wire and core			
Specified Value	—		
12. Adhesion of terminal electrode			
Specified Value	Shall not come off PC board		
Test Methods and Remarks	Applied force : 5N to X and Y directions. Duration : 5s.		
13. Resistance to vibration			
Specified Value	Inductance change : Within ±10% No significant abnormality in appearance.		
Test Methods and Remarks	The test samples shall be soldered to the test board by the reflow. Then it shall be submitted to below test conditions.		
	Frequency Range	10~55Hz	
	Total Amplitude	1.5mm (May not exceed acceleration 196m/s ²)	
	Sweeping Method	10Hz to 55Hz to 10Hz for 1min.	
	Time	X	For 2 hours on each X, Y, and Z axis.
		Y	
		Z	
Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.			
14. Solderability			
Specified Value	At least 90% of surface of terminal electrode is covered by new solder.		
Test Methods and Remarks	The test samples shall be dipped in flux, and then immersed in molten solder as shown in below table. Flux : Ethanol solution containing rosin 25%.		
	Solder Temperature	245±5℃	
	Time	5±1.0 sec.	
	※Immersion depth : All sides of mounting terminal shall be immersed.		
15. Resistance to soldering heat			
Specified Value	Inductance change : Within ±10% No significant abnormality in appearance.		
Test Methods and Remarks	The test sample shall be exposed to reflow oven at 230±5℃ for 40 seconds, with peak temperature at 260±5℃ for 5 seconds, 2 times.		
	Test board material	Glass epoxy-resin	
	Test board thickness	1.6mm	
	Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.		
16. Thermal shock			
Specified Value	Inductance change : Within ±10% No significant abnormality in appearance.		
Test Methods and Remarks	The test samples shall be soldered to the test board by the reflow. The test samples shall be placed at specified temperature for specified time by step 1 to step 4 as shown in below table in sequence. The temperature cycle shall be repeated 100 cycles.		
	Conditions of 1 cycle		
	Step	Temperature (℃)	
	1	−40±3	
	2	Room temperature	
	3	+85±2	
	4	Room temperature	
	Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.		
17. Damp heat			
Specified Value	—		

18. Loading under damp heat		
Specified Value	Inductance change : Within $\pm 10\%$ No significant abnormality in appearance.	
Test Methods and Remarks	The test samples shall be soldered to the test board by the reflow. The test samples shall be placed in thermostatic oven set at specified temperature and humidity and applied the rated current continuously as shown in below table.	
	Temperature	$60 \pm 2^{\circ}\text{C}$
	Humidity	$90 \sim 95\% \text{RH}$
	Applied current	Rated current
	Time	$500 + 24 / - 0$ hour
	Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.	
19. Low temperature life test		
Specified Value	Inductance change : Within $\pm 10\%$ No significant abnormality in appearance.	
Test Methods and Remarks	The test samples shall be soldered to the test board by the reflow. After that, the test samples shall be placed at test conditions as shown in below table.	
	Temperature	$-40 \pm 2^{\circ}\text{C}$
	Time	$500 + 24 / - 0$ hour
		Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.
20. High temperature life test		
Specified Value	—	
Test Methods and Remarks	Temperature	$105 \pm 3^{\circ}\text{C}$
	Time	$500 + 24 / - 0$ hour
		Recovery : At least 2hrs of recovery under the standard condition after the test, followed by the measurement within 48hrs.
21. Loading at high temperature life test		
Specified Value	—	
22. Standard condition		
Specified Value	Standard test condition :	
	Unless otherwise specified, temperature is $20 \pm 15^{\circ}\text{C}$ and $65 \pm 20\%$ of relative humidity.	
	When there is any question concerning measurement result: In order to provide correlation data, the test shall be condition of $20 \pm 2^{\circ}\text{C}$ of temperature, $65 \pm 5\%$ relative humidity.	
	Inductance is in accordance with our measured value.	