

Wire-wound Metal Power Inductors MCOIL™ LSEU series for General Electronic Equipment for Consumer

Code in front of Series have been extracted from Part number, which describes the segment of products, such as kinds and characteristics.

REFLOW

PART NUMBER

* Operating Temp.: -40~+125°C (Including self-generated heat)

L	S	E	U	C	2	0	1	6	K	K	T	1	R	0	M	
①	②	③	④	⑤	⑥	⑦	⑧									

① Series

Code (1)(2)(3)(4)	
LSEU	Wire-wound Metal Power Inductor for General Electronic Equipment for Consumer

(1) Product Group

Code	
L	Inductors

(3) Type

Code	
E	Metal Wire-wound (High filling type)

(2) Category

Code	Recommended equipment	Quality Grade
S	General Electronic Equipment for Consumer	3

(4) Features, Characteristics

Code	
U	High strength power choke

② Features

Code	Feature
C	Bottom electrode (Ag-resin × Sn-plate)

⑤ Packaging

Code	Packaging
T	Taping

③ Dimensions (L × W)

Code	Dimensions (L × W) [mm]
2012	2.0 × 1.25
2016	2.0 × 1.6
2520	2.5 × 2.0
3225	3.2 × 2.5

⑥ Nominal inductance

Code (example)	Nominal inductance [μH]
R47	0.47
1R0	1.0
4R7	4.7

※R=Decimal point


④ Dimensions (T)

Code	Dimensions (T) [mm]
HK	0.8
KK	1.0


⑦ Inductance tolerance

Code	Inductance tolerance
M	±20%

⑧ Internal code

STANDARD EXTERNAL DIMENSIONS / STANDARD QUANTITY

Recommended Land Patterns
Surface Mounting

- Mounting and soldering conditions should be checked beforehand.
- Applicable soldering process to these products is reflow soldering only.



Type	A	B	C
2012	0.8	0.6	1.4
2016	0.8	0.6	1.8
2520	1.0	0.8	2.2
3225	1.1	1.3	2.7

Unit : mm

Type	L	W	T	e	Standard quantity [pcs] Taping
2012HK	2.0±0.2 (0.079±0.008)	1.2±0.2 (0.047±0.008)	0.8 max (0.031 max)	0.6±0.3 (0.024±0.012)	3000
2012KK	2.0±0.2 (0.079±0.008)	1.2±0.2 (0.047±0.008)	1.0 max (0.039 max)	0.6±0.3 (0.024±0.012)	3000
2016HK	2.0±0.2 (0.079±0.008)	1.6±0.2 (0.063±0.008)	0.8 max (0.031 max)	0.6±0.3 (0.024±0.012)	3000
2016KK	2.0±0.2 (0.079±0.008)	1.6±0.2 (0.063±0.008)	1.0 max (0.039 max)	0.6±0.3 (0.024±0.012)	3000
2520KK	2.5±0.2 (0.098±0.008)	2.0±0.2 (0.079±0.008)	1.0 max (0.039 max)	0.8±0.3 (0.031±0.012)	3000
3225HK	3.2±0.2 (0.126±0.008)	2.5±0.2 (0.098±0.008)	0.8 max (0.031 max)	1.0±0.3 (0.039±0.012)	3000

Unit : mm (inch)